



Fraunhofer

TESTED[®] DEVICE

KUKA Deutschland GmbH

LBR iisy 6 till 15

Report No. KU 2302-1388

DUPLICATE

Statement of
Qualification

Product series
Particle Emission

Customer	KUKA Deutschland GmbH Zugspitzstrasse 140 86165 Augsburg Germany
Component tested	
Category:	Automation Components
Subcategory:	Robotics
Product name:	LBR iisy 6 till 15 Tested Products: <ul style="list-style-type: none">LBR iisy 15 R930 (manufacturing date: 3/21/2022)LBR iisy 6 R1300 (manufacturing date: 12/19/2022)

Random sampling of particle emissions (airborne) at representative sites

Standards/Guidelines:	ISO 14644-1, -14 The norms stated generally refer to the version valid at the time of the tests.
Test devices:	Optical particle counter: LasAir II 110 and LasAir III 110 with measuring ranges $\geq 0.1\text{ }\mu\text{m}$, $\geq 0.2\text{ }\mu\text{m}$, $\geq 0.3\text{ }\mu\text{m}$, $\geq 0.5\text{ }\mu\text{m}$, $\geq 1.0\text{ }\mu\text{m}$ and $\geq 5.0\text{ }\mu\text{m}$
Test environment parameters:	<ul style="list-style-type: none">Cleanroom Air Cleanliness Class (according to ISO 14644-1):..... ISO 1Airflow velocity:.....0.45 m/sAirflow pattern:..... vertical laminar flowTemperature:22 °C \pm 0.5 °CRelative humidity: 45 % \pm 5 %
Test procedure parameters:	<ul style="list-style-type: none">Capacity:40 % and 80 % of maximum velocityBreak between cycles:0sOperation of each axis:..... separatelyMovement of each axis:<ul style="list-style-type: none">– Axis 1: -150° to 150°– Axis 2: -160° to -40°– Axis 3: -90° to 90°– Axis 4: -150° to 150°– Axis 5: -90° to 90°– Axis 6: -180° to 180°

Test result / Classification	When operated under the specified test conditions, the robot series LBR iisy 6 till 15 is suitable for use in cleanrooms fulfilling the specifications of the following Air Cleanliness Classes according to ISO 14644-1:
------------------------------	---

Test parameter(s)	Air Cleanlines Class
40 % of maximum velocity	5
80 % of maximum velocity	5
Overall result	5

Please note: Transport damages, incorrect installation, oil leakage, aging behavior, corrosion etc. can influence the test result.

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA	KU 2302-1388 Report No. first document	Stuttgart, February 22, 2023 Place, date of first document issued
Department of Ultraclean Technology and Micromanufacturing	-- Report No. current document	-- Place, current date
Nobelstrasse 12 70569 Stuttgart Germany	on behalf of Dr.-Ing. Frank Bürger, Project Manager Fraunhofer IPA	