



Fraunhofer

**TESTED[®]
DEVICE**

SG Armaturen AS
Interpon 610 AC
Report No. SG 2303-1398

DUPLICATE

Statement of
Qualification

Single product
Chemical Resistance

Customer

SG Produktion A/S
Egestubben 16-26
5270 Odense N
Denmark

Component tested

Category:

Materials

Subcategory:

Coatings

Product name:

Interpon 610 AC
(manufacturing date: 3/2023; color: white; article number: 0000104375)

Chemical resistance test

Standards/Guidelines:

VDI 2083 Part 17; ISO 2812-1; ISO 4628-1
The norms stated generally refer to the version valid at the time of the tests.

Testing equipment:

- Microscope
- Camera

Test environment parameters:

Temperature:.....22 °C ± 0.5 °C

Test procedure parameters:

Immersion method

- Chemicals:.....Formalin 37 %
.....Ammoniac 25 %
.....Hydrogen peroxide 30 %
.....Sulfuric acid 5 %
.....Phosphoric acid 30 %
.....Peracetic acid 15 %
.....Hydrochloric acid 5 %
.....Isopropanol 100 %
.....Sodium hydroxide 5 %
.....Sodium hypochlorite 5 %
- Incubation time: 1 h, 3 h, 6 h, 24 h

Test result / Classification

The chemical resistance of Interpon 610 AC was classified according to ISO 4628-1 and VDI 2083 Part 17 with the following result:

Chemical resistance	1 h	3 h	6 h	24 h
Formalin 37 %	0	0	0	0
Ammoniac 25 %	0	0	0	0
Hydrogen peroxide 30 %	0	0	0	0
Sulfuric acid 5 %	0	0	0	0
Phosphoric acid 30 %	0	0	0	0
Peracetic acid 15 %	0	1	1	2
Hydrochloric acid 5 %	0	0	0	0
Isopropanol 100 %	0	0	0	0
Sodium hydroxide 5 %	0	0	0	0
Sodium hypochlorite 5 %	0	0	0	0

The classification is based on a worst-case consideration. In the process, damage was assessed according to the classification system used in ISO 4628-1 and VDI 2083 Part 17:

0 = excellent
1 = very good
2 = good

3 = weak
4 = very weak
5 = none

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

Department of Ultraclean Technology and Micromanufacturing

Nobelstrasse 12
70569 Stuttgart
Germany

SG 2303-1398

Report No. first document

--

Report No. current document

on behalf of

Dr.-Ing. Frank Bürger, Project Manager Fraunhofer IPA

Stuttgart, November 16, 2023

Place, date of first document issued

--

Place, current date

