



# Fraunhofer

## TESTED<sup>®</sup> DEVICE

igus GmbH  
SKS28.068.02.1

**Report No. IG 2411-1575**

Statement of  
Qualification

Single product  
Particle Emission  
in Dry-Cleanroom  
with Pre-aging

Customer

igus GmbH  
Spicher Strasse 1a  
51147 Cologne  
Germany

Tested product

Category: Energy Supply

Subcategory: Cable Guiding Systems

Product name: SKS28.068.02.1 of the e-skin serial SKS28  
(manufacturing date: 10/9/2023; color: white; article number: SKS28.068.02.1; serial number: SKS28; batch number: 70957617)

Random particle emission measurements (airborne) at representative points of the product in the dry-cleanroom with Pre-aging under dry room conditions

Standards/guidelines: ISO 14644-1, -14  
The norms stated generally refer to the version valid at the time of the tests.

Test devices: Optical particle counter:  
LasAir II 110 and LasAir III 110 with measuring ranges  $\geq 0.1\text{ }\mu\text{m}$ ,  $\geq 0.2\text{ }\mu\text{m}$ ,  $\geq 0.3\text{ }\mu\text{m}$ ,  $\geq 0.5\text{ }\mu\text{m}$ ,  $\geq 1.0\text{ }\mu\text{m}$  and  $\geq 5.0\text{ }\mu\text{m}$

Test environment parameters:

- Dry-Cleanroom Air Cleanliness Class (according to ISO 14644-1): ..... ISO 3
- Airflow velocity: .....  $0.1\text{ m/s} \pm 0.05\text{ m/s}$
- Airflow pattern: ..... displacement flow
- Room temperature: .....  $22\text{ }^{\circ}\text{C} \pm 1\text{ }^{\circ}\text{C}$
- Relative humidity/dew point: .....  $-40\text{ }^{\circ}\text{C} \pm 2\text{ }^{\circ}\text{C}$

Test procedure parameters:

- Pre-aging in dry room:
  - Insertion in dry room: ..... 1/31/2024; 7:10 am
  - Operation time in dry room: ..... 10 months
  - Cycles during operation time: ..... 15.102.956
- Bending radius: .....  $r = 55\text{ mm}$
- Stroke length: .....  $h = 750\text{ mm}$
- Parameter set 1: .....  $v_1 = 0.5\text{ m/s}$ ;  $a_1 = 1.0\text{ m/s}^2$
- Parameter set 2: .....  $v_2 = 1.0\text{ m/s}$ ;  $a_2 = 2.0\text{ m/s}^2$
- Parameter set 3: .....  $v_3 = 2.0\text{ m/s}$ ;  $a_3 = 4.0\text{ m/s}^2$

Test result / Classification

When operated under the specified test conditions (room temperature of  $22\text{ }^{\circ}\text{C} \pm 1\text{ }^{\circ}\text{C}$ ; dew point:  $-40\text{ }^{\circ}\text{C} \pm 2\text{ }^{\circ}\text{C}$ ), the SKS28.068.02.1 of the e-skin serial SKS28 is suitable for use in dry-cleanrooms fulfilling the specifications of the following Air Cleanliness Classes according to ISO 14644-1:

Pre-aging, operation time in dry room: 10 months, 15.102.956 cycles	
Test parameter(s)	Air Cleanlines Class
$v_1 = 0.5\text{ m/s}$ ; $a_1 = 1.0\text{ m/s}^2$	4
$v_2 = 1.0\text{ m/s}$ ; $a_2 = 2.0\text{ m/s}^2$	4
$v_3 = 2.0\text{ m/s}$ ; $a_3 = 4.0\text{ m/s}^2$	4
Overall result	4

Please note: Transport damages, incorrect installation, aging behavior etc. can influence the test result.

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

Department of Ultraclean Technology and Micromanufacturing


Nobelstrasse 12  
70569 Stuttgart  
Germany

IG 2411-1575  
Report No. first document

Stuttgart, February 3, 2025  
Place, date of first document issued

--  
Report No. current document

--  
Place, current date

on behalf of   
Dr.-Ing. Frank Bürger, Project Manager Fraunhofer IPA