



Fraunhofer

TESTED[®] DEVICE

igus GmbH
E6.29.060J.100.0
Report No. IG 2402-1498

DUPLIKAT

Statement of
Qualification

Single product
Particle emission
in Dry-Cleanroom
Aging behavior

Customer	igus GmbH Spicherstrasse 1a 51147 Cologne Germany
Tested product	
Category:	Energy Supply
Subcategory:	Cable Guiding Systems
Product name:	E6.29.060J.100.0 – series E6.29 (manufacturing date: 10/2023; color: black/yellow; article number: E6.29.060J.100.0; serial number: E6.29)
Random particle emission measurements (airborne) at representative points of the product in the dry-cleanroom during continuous operation to determine the aging behavior	
Standards/guidelines:	ISO 14644-1, -14 The norms stated generally refer to the version valid at the time of the tests.
Test equipment:	Optical particle counter: LasAir II 110 and LasAir III 110 with measuring ranges $\geq 0.1\text{ }\mu\text{m}$, $\geq 0.2\text{ }\mu\text{m}$, $\geq 0.3\text{ }\mu\text{m}$, $\geq 0.5\text{ }\mu\text{m}$, $\geq 1.0\text{ }\mu\text{m}$ and $\geq 5.0\text{ }\mu\text{m}$
Test environment parameters:	<ul style="list-style-type: none">Dry-Cleanroom Air Cleanliness Class (according to ISO 14644-1): ISO 3Airflow velocity: $0.1\text{ m/s} \pm 0.05\text{ m/s}$Airflow pattern: displacement flowRoom temperature: $22\text{ }^{\circ}\text{C} \pm 1\text{ }^{\circ}\text{C}$Relative humidity/dew point: $-40\text{ }^{\circ}\text{C} \pm 2\text{ }^{\circ}\text{C}$
Test procedure parameters:	<ul style="list-style-type: none">Continuous operation for determination of the aging behavior:<ul style="list-style-type: none">– Measurement 1,new:..... after running-in period 24 h, 0 cylces– Measurement 2, after 2 months:3,223,447 cycles– Measurement 3, after 4 months: 5,071,531 cycles– Measurement 4, after 6 months:7,488,714 cycles– Measurement 5, after 8 months:10,017,858 cycles– Measurement 6, after 10 months: 15,102,956 cycles– Measurement 7, after 12 months: 20,086,109 cycleBending radius and stroke length: $r = 240\text{ mm}$; $h = 750\text{ mm}$Parameter set 1 to 3:<ul style="list-style-type: none">– Velocity:.....$v_1 = 0.5\text{ m/s}$– Acceleration: $a_1 = 1.0\text{ m/s}^2$– Velocity:.....$v_2 = 1.0\text{ m/s}$– Acceleration: $a_2 = 2.0\text{ m/s}^2$– Velocity:.....$v_3 = 2.0\text{ m/s}$– Acceleration: $a_3 = 4.0\text{ m/s}^2$

Test result / Classification	When operated under the specified test conditions (room temperature of $22\text{ }^{\circ}\text{C} \pm 1\text{ }^{\circ}\text{C}$; dew point: $-40\text{ }^{\circ}\text{C} \pm 2\text{ }^{\circ}\text{C}$), the cable guiding system E6.29.060J.100.0 of the series Serie E6.29 is suitable for use in dry-cleanrooms fulfilling the specifications of the following Air Cleanliness Classes according to ISO 14644-1:
------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------


Aging behavior during continuous operation in Dry-Cleanroom, Test parameter(s)	Air Cleanlines Class
Test 1, new (after running-in period, 0 cycles)	4
Test 2, after 2 months (3.2 Mio. cycles)	4
Test 3, after 4 months (5.1 Mio. cycles)	4
Test 4, after 6 months (7.5 Mio. cycles)	5
Test 5, after 8 months (10.0 Mio. cycles)	5
Test 6, after 10 months (15.1 Mio. cycles)	5
Test 7, after 12 months (20.1 Mio. cycles)	4
Overall result	5

Note 1: The results refer to the three test parameter sets: (0.5m/s, 1.0m/s²), (1.0m/s, 2.0m/s²), (2.0m/s, 4.0m/s²)

Note 2: Transport damages, incorrect installation, aging behavior, corrosion etc. can influence the test result.

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA	IG 2402-1498 Report No. first document	Stuttgart, March 28, 2025 Place, date of first document issued
Department of Ultraclean Technology and Micromanufacturing	-- Report No. current document	-- Place, current date
Nobelstrasse 12 70569 Stuttgart Germany	on behalf of Dr.-Ing. Frank Bürger, Project Manager Fraunhofer IPA	

This document only applies to the named product in its original state and is valid for a period of 5 years from the date the first document was issued. The document can be verified under www.tested-device.com.