



valid until: February 11, 2031

# Fraunhofer

## TESTED<sup>®</sup> DEVICE

Murrplastik Systemtechnik GmbH  
MPOD Energy Chain

**Report No. MU 2601-1720**

DUPLICATE

Statement of  
Qualification

Single product  
Particle Emission  
in Cleanroom  
(atmospheric)

# Statement of Qualification · Single product

**Customer**  
 Murrplastik Systemtechnik GmbH  
 Dieselstrasse 10  
 71570 Oppenweiler  
 Germany

**Tested product**  
 Category: Energy Supply  
 Subcategory: Cable Guiding Systems  
 Product name: Cleanroom MPOD Energy Chain  
 (manufacturing date: 10/28/2025; color: white; article number: MPP201203002)

## Test result / Classification

The Cleanroom MPOD Energy Chain is suitable for use under the specified test parameters (room temperature: 22 °C ± 0.5 °C; relative humidity: 45 % ± 5 %) in cleanrooms of the following Air Cleanliness Classes according to ISO 14644-1:

Test parameter(s)	Air Cleanliness Class
$v_1 = 0.5 \text{ m/s}; a_1 = 1.0 \text{ m/s}^2$	1
$v_2 = 1.0 \text{ m/s}; a_2 = 2.0 \text{ m/s}^2$	1
$v_3 = 2.0 \text{ m/s}; a_3 = 4.0 \text{ m/s}^2$	1
<b>Overall result</b>	<b>1</b>

Please note: Transport damages, incorrect installation, aging behavior, etc. can influence the test result.

## Random sampling of particle emissions (airborne) at representative sites in cleanroom under atmospheric conditions

Standards/guidelines: ISO 14644-1, -14  
 The norms stated generally refer to the version valid at the time of the tests.

Test equipment: Optical particle counter:  
 LasAir II 110 and LasAir III 110 with measuring ranges  $\geq 0.1 \mu\text{m}$ ,  $\geq 0.2 \mu\text{m}$ ,  $\geq 0.3 \mu\text{m}$ ,  $\geq 0.5 \mu\text{m}$ ,  $\geq 1.0 \mu\text{m}$  and  $\geq 5.0 \mu\text{m}$

Test environment parameters:

- Cleanroom Air Cleanliness Class (according to ISO 14644-1):..... ISO 1
- Airflow velocity:..... 0.45 m/s
- Airflow pattern:..... vertical laminar flow
- Room temperature: ..... 22 °C ± 0.5 °C
- Relative humidity: ..... 45 % ± 5 %

Test procedure parameters:

- Bending radius: ..... r = 125 mm
- Stroke length:..... s = 820 mm
- Parameter Set 1:.....  $v_1 = 0.5 \text{ m/s}; a_1 = 1.0 \text{ m/s}^2$
- Parameter Set 2:.....  $v_2 = 1.0 \text{ m/s}; a_2 = 2.0 \text{ m/s}^2$
- Parameter Set 3:.....  $v_3 = 2.0 \text{ m/s}; a_3 = 4.0 \text{ m/s}^2$

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

MU 2011-1190  
 Report No. first document

Stuttgart, December 18, 2020  
 Place, date of first document issued

Business unit Testing and Certification

MU 2601-1720  
 Report No. current document

Stuttgart, February 11, 2026  
 Place, current date

Nobelstrasse 12  
 70569 Stuttgart  
 Germany

on behalf of   
 Dr.-Ing. Frank Bürger, head of business unit Testing and Certification