



# Fraunhofer

## TESTED<sup>®</sup> DEVICE

Ziehl-Abegg SE  
ZAmid PAPA LGF40 blue  
**Report No. ZI 2603-1743**

DUPLICATE

Statement of  
Qualification

Single product  
Outgassing Behavior  
Inorganic Acids

# Statement of Qualification · Single product

**Customer**  
 Ziehl-Abegg SE  
 Heinz-Ziehl-Strasse  
 74653 Künzelsau  
 Germany

**Tested product**  
 Category: Materials  
 Subcategory: Plastics  
 Product name: ZAmid PAPA LGF40 blue  
 (manufacturing date: 3/2026; color: blue; article number: 00414179)

## Emission chamber measurements with gas impingement in combination with ion chromatography (IC)

Standards/guidelines: ISO 14644-8, -15  
 The norms stated generally refer to the version valid at the time of the tests.

Test equipment:
 

- Measuring station:.....Metrohm Professional IC 850
- Sampling chamber:.....Markes International µCTE

Sample storage:
 

- Pre-conditioning
  - Cleanroom Air Cleanliness Class (according to ISO 14644-1):..... ISO 1
  - Airflow velocity:.....0.45 m/s
  - Airflow type:..... vertical laminar flow
  - Temperature: .....22 °C ± 0.5 °C
  - Relative humidity: ..... 45 % ± 5 %
  - Purified air: ..... VOC-filtered

Test procedure parameters: Outgassing test temperature:..... 23 °C

## Test result / Classification

The outgassing behavior of ZAmid PAPA LGF40 blue at the stated temperature was investigated according to ISO 14644-15. Based on the outgassing rates determined for the specific surfaces, the following material classification was made for the corresponding Contaminant Category:

Contaminant Category (x)	SER <sub>a</sub> <sup>1)</sup> 23 °C [g/(m <sup>2</sup> * s)]	ISO-ACC <sub>m</sub> Class (x)
Fluoric acid (HF)	< 2.9 x 10 <sup>-9</sup>	< -8.5
Hydrochloric acid (HCl)	< 2.9 x 10 <sup>-9</sup>	< -8.5
Hydrobromic acid (HBr)	< 2.9 x 10 <sup>-9</sup>	< -8.5
Nitric acid (HNO <sub>3</sub> )	< 2.9 x 10 <sup>-9</sup>	< -8.5
Phosphoric acid (H <sub>3</sub> PO <sub>4</sub> )	< 2.9 x 10 <sup>-9</sup>	< -8.5
Sulfuric acid (H <sub>2</sub> SO <sub>4</sub> )	< 2.9 x 10 <sup>-9</sup>	< -8.5

<sup>1)</sup>The emission rate is calculated using the detected concentration based on the external standard calibration, the analyzed sample surface area or number of samples, the volume of the impingement solution and the sampling duration.

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.