





Fraunhofer TESTED® DEVICE DENSO WAVE Inc. PVC (S-1) Report No. DE 2006-1161

Statement of Qualification

Single product Biological Resistance

Statement of Qualification • Single product

Customer

DENSO WAVE Inc. 1, Yoshiike, Kusaki, Agui-cho, Chita-gun 470-2297 Aichi Japan

Test result/Classification

result:

Biological

Overall res

0 = excellent

0 = excellent

1 = good

Component tested

Category:	Materials
Subcategory:	Plastics
Product name:	PVC (S-1) (manufacturing date: 4/2020; color: gray; serial number: PLATE_2020-15)

Biological resistance test

Standards/Guidelines:

Test environment parameters:

Test procedure parameters:

	ISO 846 The norms stated generally refer to the version valid at the time of the tests.		
	Microbiological laboratory:		
	• Procedure A (resistance to fungi) using spore suspension of spores containing the following test strains:		
	 Aspergillus niger ASM 1957 Chaetomium globosum ASM 1962 Paecilomyces variotii ASM 1961 		
	• Procedure C (resistance to bacteria) using bacteria suspension containing the following test strain: <i>Pseudomonas aeruginosa</i> DSM 1253		

• Incubation at 29 ± 1 °C with a relative humidity of ≥ 95 %; visually inspection after four (4) weeks

> The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

Report No. first document

Department of Ultraclean Technology and Micromanufacturing

Nobelstrasse 12 70569 Stuttgart Germany



Report No. current document

DE 2006-1161

on behalf of RTRi Dr.-Ing. Frank Bürger, Project Manager Fraunhofer IPA



The biological resistance of PVC (S-1) regarding to growth intensity was investigated in accordance with ISO 846 and classified with the following

esistance	Growth intensity	Classification
(resistance to fungi)	0	excellent
(resistance to bacteria)	2	weak
ult	weak	

The classification is based on a worst-case consideration of the Procedures A and C. In the process, growth intensity was assessed according to the classification system used in ISO 846:

Classification: fungi (Procedure A) 2, 3 = weak 4, 5 = none 1a, 1b, 1c = good

Classification: bacteria (Procedure C)

2 = weak3 = none

Stuttgart, July 15, 2015

Place, date of first document issued

Stuttgart, November 4, 2020 Place, current date

This document only applies to the named product in its original state and is valid for a period of 5 years from the current date the document was issued. The document can be verified under www.tested-device.com.