



**Fraunhofer**

**TESTED<sup>®</sup>  
DEVICE**

DENSO WAVE Inc.  
SUS630-H900 (Cutting)  
**Report No. DE 2006-1161**

DUPLICATE

Statement of  
Qualification

Single product  
Chemical Resistance

Statement of Qualification · Single product

Customer

DENSO WAVE Inc.  
1, Yoshiike, Kusaki, Agui-cho, Chita-gun  
470-2297 Aichi  
Japan

Component tested

Category:

Materials

Subcategory:

Metals

Product name:

SUS630-H900 (Cutting)  
(manufacturing date: 4/2020; serial number: PLATE\_2020-03)

Chemical resistance test

Standards/Guidelines:

VDI 2083 Part 17; ISO 2812-1; ISO 4628-1  
The norms stated generally refer to the version valid at the time of the tests.

Testing equipment:

- Microscope
- Camera

Test environment parameters:

Temperature:.....22 °C ± 0.5 °C

Test procedure parameters:

Immersion method:

- Chemicals:.....Formalin 37 %  
.....Ammoniac 25 %  
.....Hydrogen peroxide 30 %  
.....Sulfuric acid 5 %  
.....Phosphoric acid 30 %  
.....Peracetic acid 15 %  
.....Hydrochloric acid 5 %  
.....Isopropanol 100 %  
.....Sodium hydroxide 5 %  
.....Sodium hypochlorite 5 %
- Incubation time: .....1 h, 3 h, 6 h, 24 h

Test result / Classification

The chemical resistance of SUS630-H900 (Cutting) was classified according to ISO 4628-1 and VDI 2083 Part 17 with the following result:

Chemical resistance	1 h	3 h	6 h	24 h
Formalin 37 %	0	0	0	0
Ammoniac 25 %	0	0	0	0
Hydrogen peroxide 30 %	0	0	0	0
Sulfuric acid 5 %	0	0	0	1
Phosphoric acid 30 %	0	0	0	0
Peracetic acid 15 %	0	0	0	0
Hydrochloric acid 5 %	0	2	2	2
Isopropanol 100 %	0	0	0	0
Sodium hydroxide 5 %	0	0	0	0
Sodium hypochlorite 5 %	0	0	0	0

The classification is based on a worst-case consideration. In the process, damage was assessed according to the classification system used in ISO 4628-1 and VDI 2083 Part 17:

0 = excellent  
1 = very good  
2 = good

3 = weak  
4 = very weak  
5 = none

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing Engineering and Automation IPA

DE 1409-725  
Report No. first document


Stuttgart, July 15, 2015  
Place, date of first document issued

Department of Ultraclean Technology and Micromanufacturing

DE 2006-1161  
Report No. current document

Stuttgart, November 4, 2020  
Place, current date

Nobelstrasse 12  
70569 Stuttgart  
Germany

on behalf of   
Dr.-Ing. Frank Bürger, Project Manager Fraunhofer IPA

This document only applies to the named product in its original state and is valid for a period of 5 years from the current date the document was issued. The document can be verified under [www.tested-device.com](http://www.tested-device.com).