

Fraunhofer TESTED® DEVICE

SUS316L (Grinding) Report No. DE 2006-1161

Single product Chemical Resistance

This document only applies to the named product in its original state and is valid for a period of 5 years from the current date the document was issued. The document can be verified under www.tested-device.com.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Qualification Certificate

This is to certify that the product mentioned above, provided by

DENSO WAVE Inc. Aichi, Japan

has been awarded a Fraunhofer certificate TESTED DEVICE bearing the report number DE 2006-1161.

The chemical resistance of SUS316L (Grinding) was classified according to ISO 4628-1 and VDI 2083 Part 17 with the following result:

| Chemical resistance | | | |
|------------------------|-----------|-------------------------|-----------|
| Formalin 37 % | excellent | Peracetic acid 15 % | excellent |
| Ammoniac 25 % | excellent | Hydrochloric acid 5 % | very weak |
| Hydrogen peroxide 30 % | excellent | Isopropanol 100% | excellent |
| Sulfuric acid 5 % | excellent | Sodium hydroxide 5 % | excellent |
| Phosphoric acid 30 % | excellent | Sodium hypochlorite 5 % | excellent |

DE 1409-725 Report No. first document Stuttgart, July 15, 2015 Place, date of first document issued

DE 2006-1161 Report No. current document

Place, date of first document issued

Stuttgart, November 4, 2020 Place, current date



on behalf of Dr.-Ing. Frank Bürger, Project Manager Fraunhofer IPA