



Fraunhofer
TESTED[®]
DEVICE
LAPP KOREA LLC
FD 8711 C MC 7x0.34
Report No. LA 2410-1570

Statement of
Qualification

Single product
Outgassing Behavior
VOC/SVOC

DUPPLICATE

Statement of Qualification • Single product

Customer

LAPP KOREA LLC
42, Jangangongdan 8-gil, Jangan-myeon
18579 Hwaseong-si, Gyeonggi-do,
Republic of Korea

Test result / Classification

The outgassing behavior of the cable system CLEANROOM FD 8711 C MC 7 x 0.34 mm² at the stated temperatures was investigated according to ISO 14644-15. Based on the outgassing rates determined for the specific units, the following material classification was made for the corresponding Contaminant Category:

Tested product

Category: Energy Supply
Subcategory: Cable Systems
Product name: CLEANROOM FD 8711 C MC 7 x 0.34 mm²
(manufacturing date: 9/9/2024; color: black; serial number: 85133400;
batch number: E/37; length: 1 m)

Contaminant Category (x)	SER _u ¹⁾ 23 °C [g/unit*s]	ISO-ACC _e Class (x) based on 23 °C
VOC	1.7 x 10 ⁻⁹	-8.8
SVOC	< 2.8 x 10 ⁻¹³	< -12.6
Amines	< 2.8 x 10 ⁻¹³	--
Organophosphates	< 2.8 x 10 ⁻¹³	--
Siloxanes	< 2.8 x 10 ⁻¹³	--
Phthalates	< 2.8 x 10 ⁻¹³	--

¹⁾SER_u: Unit-specific emission rate

Emission chamber measurements with purge-and-trap thermodesorption method and gas chromatography combined with mass spectrometry (TD-GC/MS)

Standards/guidelines: ISO 14644-8, -15; ISO 16000-6, -9, -11, -25; VDI 2083 Part 17
The norms stated generally refer to the version valid at the time of the tests.

Test equipment:

- Measuring station: PerkinElmer Clarus 600, Clarus SQ8, ATD 650

Sample storage:

- Pre-conditioning:
 - Cleanroom Air Cleanliness Class (according to ISO 14644-1): ISO 1
 - Airflow velocity: 0.45 m/s
 - Airflow type: vertical laminar flow
 - Temperature: 22 °C ± 0.5 °C
 - Relative humidity: 45 % ± 5 %
 - Purified air: VOC-filtered

Test procedure parameters:

- Retention range (VOC): C6 to C16
- Outgassing test temperature: 23 °C

The measuring devices used for the qualification tests are calibrated at regular intervals; their results can be traced back to national and international standards. In cases where no national standards exist, the test procedure implemented complies with the technical regulations and norms applicable at the time of the test. The relevant documentation can be viewed on request at any time.

Detailed information and parameters of the test environment can be found in the Fraunhofer IPA test report.

Fraunhofer Institute for Manufacturing
Engineering and Automation IPA

Department of Ultraclean Technology
and Micromanufacturing

Nobelstrasse 12
70569 Stuttgart
Germany

LA 2410-1570
Report No. first document

Stuttgart, February 20, 2025
Place, date of first document issued

--
Report No. current document

--
Place, current date

on behalf of 
Dr.-Ing. Frank Bürger, Project Manager Fraunhofer IPA

This document only
applies to the named
product in its original state
and is valid for a period of
5 years from the date the
first document was issued.
The document can be
verified under
www.tested-device.com